

## PRO R SLIM 30-40-56-80-100

### MULTI-POSITION WALL-HUNG ELECTRIC STORAGE WATER HEATER



- Easy and flexible installation
- Two different diameters: regular [450mm] and slim [353mm]
- Exclusive enameled tank protection
- Horizontal installation
- External temperature regulation
- Large anticorrosion magnesium anode
- High efficiency insulation material
- Easy maintenance
- Wide range of capacities
- Worry-free TSS Total Safety System
- Suitable for counter-ceiling hidden installation

*multi-position  
mounting*

### Technical data - Overall dimensions

	Unit	PRO R S 30 SHE	PRO R S 40 SHE	PRO R S 56 SHE	PRO R S 80 HE	PRO R S 100 HE		PRO R S 30 SHE	PRO R S 40 SHE	PRO R S 56 SHE	PRO R S 80 HE	PRO R S 100 HE
Capacity	L	30	40	56	80	100	a mm	526	754	962	782	934
Power	kW	3	3	3	3	3	b mm	229	367	576	337	489
Voltage	V	230	230	230	230	230	c mm	353	353	353	450	450
Heating time ( $\Delta T=35^{\circ}C$ )	h:min	0:26	0:34	0:48	1:09	1:26	d mm	373	373	373	470	470
Max. Working Temperature	$^{\circ}C$	65	65	65	65	65	e mm	79	79	79	127	127
Heat dispersion	kWh/24hr	0.74	0.97	1.19	1.41	1.60						
Max. Working Pressure	bar	8	8	8	8	8						
Net Weight	Kg	13	17	21	23	27						
Inner Tank Steel Thickness (average)	mm	1.8	1.8	1.8	1.8	1.8						

DESCRIPTION	PRO R S 30 SHE	PRO R S 40 SHE	PRO R S 56 SHE	PRO R S 80 HE	PRO R S 100 HE
CODE	3626006	3626026	3626027	3626028	3626029

INSTALLATION wall - ceiling horizontal

### All direction mounting

