

POOL & SPA pH & CL TEST SOLUTION FOR SWIMMING POOL



Instructions

- Fill pool water in the TEST KIT CELLS
- Use 5 drops of test solution
- Read values by comparing to the colour standards on the TEST KIT

Chlorine value should be : 1.0 – 1.5 ppm

pH Value should be : 7.2 – 7.6



Code	Model	Packing		
24001610095	pH & CL Refill	30 CC / Bottle		



HYDROCHLORIC ACID



Code	Model	Description	Packing		
24001610120	Hydrochloric Acid	3 ลิตร ต่อ น้ำ 100 ลิตร เมื่อค่า pH สูงกว่า 7.6 3 litres per 100 m ³ of water when pH is higher than 7.6	25 kgs / drum		



SODA ASH



Code	Model	Description	Packing		
24003100010	Soda Ash - 25	2 กก. ต่อ น้ำ 100 ลิตร เมื่อค่า pH ต่ำกว่า 7.2 Use 2 kgs per 100 m ³ of water if the pH level is lower than 7.2	25 kgs/bag		
24003100015	Soda Ash - 40		40 kgs/bag		



VINYL ADHESIVE



Code	Model	Description	Packing		
22213100010	Vinyl Adhesive	กาวปะผ้าไวนิลใต้น้ำ Vinyl Liner Glue	118.3 ml./can		



“POXY PUTTY” TILE GLUES



- These two-part Epoxy Putty kits vary in size and include equal volumes of Part A: Base and Part B: Catalyst.
- Sea Goin® Poxy Putty can be used for any repair job where the surfaces are wet, dry or even underwater!
- It can be used to patch, seal, caulk, mend or fasten most materials. It will bond metals, wood, fiberglass, concrete, ferrocement and most plastics, **except** polypropylene, polyethylene, PVC or Teflon.

Features:

- Cures off-white in color
- Can be sanded or painted
- Mix ratio is 1:1
- Sets up in 3-4 hours at 75° F.
- Cures in 24 hours at 75° F.

Code	Model	Description	Packing		
23613100005	Poxy Putty	กาวปะกระเบื้องใต้น้ำ Underwater Swimming Pool Tiles Glue	340 grams/can		